

Sea crane



Model	H051-3	H061-3	H081-3	H121-3	H201-5	H251-5	H301-5	H331L-4	H401L-4	H402-6
Crane capacity(tm)	45	50.8	72.6	127	160	227	270	311.5	362	347
Max. outreach(m)	9.09	9.6	9.6	12	14.1	13.6	13.7	17	16.1	17.4

Model	H051-3	H061-3	H081-3	H121-3	H201-5	H251-5	H301-5	H331L-4	H401L-4	H402-6
Crane capacity(kNm)	45	50.8	72.6	127	160	227	270	311.5	362	347
Max, outreach(m)	9.09	9.6	9.6	12	14.1	13.6	13.7	17	16.1	17.4

Lifting capacity(m/kg)	4.1/1120	3.8/1330	4.3/1720	5.4/2400	5.1/3200	5.2/4450	5.3/5200	8.5/3750	8.6/4300	5.2/6800
	5.7/760	5.4/900	6.0/1180	7.6/1700	6.8/2220	6.8/3250	6.9/3800	10.6//2820	10.4//3400	7.2//4600
	7.3/570	7.3/650	7.8/870	9.8/1200	8.6/1640	8.5/2500	8.5/3000	12.7/2260	12.5/2700	9.2/3400
	9.0/450	9.2/500	9.6/700	12.0/1000	10.4/1280	10.2/2040	10.2/2460	14.9/1860	14.2/2300	11.3/2600
					12.3/1040	11.9/1720	11.9/2080	17.0/1620	16.1/2000	13.3/2120
					14.1/900	13.5/1500	13.6/1800			15.4/1780
										17.4/1560

Weight(kg)	710	1040	1280	2350	2930	3400	3600	4600	5200	4810
Lifting speed(sec)	13	12	15	26	33	51	51	40	50	45
Rated working pressure(bar)	260	250	250	250	260	240	250	250	250	260
Rated oil flow(ℓ/min)	25	35	35	40	40	40	40	60	60	60

Slewing angle(°)	410°	400°	400°	400°	400°	400°	360° Continuous	360° Continuous	360° Continuous	360° Continuous
------------------	------	------	------	------	------	------	--------------------	--------------------	--------------------	--------------------

Max. heel/trim angle(°)	5°/Heel, 2°/Trim					5°/Heel, 2°/Trim				
-------------------------	------------------	--	--	--	--	------------------	--	--	--	--

Slewing torque(kNm)	6.2	11.1	14.2	31.6	45.5	45.5	48.1	56	62.1	62.6
---------------------	-----	------	------	------	------	------	------	----	------	------

Slewing speed(°/sec)	7.2					7.2				
----------------------	-----	--	--	--	--	-----	--	--	--	--

Net required power(kw)	10.6	14.3	14.3	16	16.3	15.7	16.3	24.5	24.5	25.5
------------------------	------	------	------	----	------	------	------	------	------	------